

# DB307/311/300 1-phase

## DESCRIPTION

Dutair blowers for pressure and vacuum are compact machines consisting of an electric motor with a built-on pump housing. The rotational speed of the impeller creates a high compression of the internal air, resulting in a vacuum at the inlet and pressure at the outlet of the blower.

This process works without any contact, thus eliminating wear and the need for lubrication.

## FEATURES

- compressor and vacuum pump in a single unit
- robust
- oil-free
- low noise levels
- low vibration levels
- maintenance free
- vertical mounting with in- / outlet pointing upwards possible
- integrated silencers
- many different applications

## BENEFITS

- high flow and high pressure out of a single phase voltage supply
- accurate performance curves allows engineering with smaller reserve capacity
- detailed sound level data for acoustic purposes
- Dutair blower motors are fitted with PTC thermistors as standard
- a variety of modifications possible for non-standard applications

**DB309 3-phase****DB300**



## GENERAL TECHNICAL DATA

		DB307 1-phase		DB311 1-phase		DB300
		50 Hz	60 Hz	50 Hz	60 Hz	bare shaft
Power <sup>①</sup>	kW	0.75	0.85	1.1	1.3	max. 1.3
Voltage <sup>②</sup>	V	230	230	230	230	-
Current	A	5.8	6.5	7.0	8.0	-
Revolutions	/min	2860	3390	2830	3300	1750...4500
Protection class <sup>③</sup>		IP55	IP55	IP55	IP55	-
PTC Thermistors <sup>④</sup>	°C	140	140	140	140	-
Sound pressure <sup>⑦</sup>	dB(A)	60.0	65.3	63.2	65.8	-
Weight	kg	15	15	15	15	10

## DB307/311/300 1-phase


### PERFORMANCE

Static pressure difference between in- and outlet  $\Delta p_s$  against airflow  $Q$  at an ambient condition of 1013 mbar and 20 °C. All duty points on characteristics curves are in thermal equilibrium<sup>®</sup>. Flow is rated in Nm<sup>3</sup>/h defined as air, 1013 mbar and 0 °C. Tolerance +/-3%. See notes on page 6.




### TEMPERATURE RISE

Temperature rise  $\Delta T$  measured directly at in- and outlet. Ambient condition of 1013 mbar and 20 °C. All duty points on characteristics curves are in thermal equilibrium<sup>®</sup>. Tolerance +/-5 °C.



### POWER



Motor power  $P$  delivered at impeller shaft. Ambient condition of 1013 mbar and 20 °C. All duty points on characteristics curves are in thermal equilibrium<sup>®</sup>. Tolerance +/-5 %. Accurate data on current consumption for specific duty points available on request.



## DB307/311/300 1-phase


### PERFORMANCE

Static pressure difference between in- and outlet  $\Delta p_s$  against airflow  $Q$  at an ambient condition of 1013 mbar and 20 °C. All duty points on characteristics curves are in thermal equilibrium<sup>®</sup>. Flow is rated in Nm<sup>3</sup>/h defined as air, 1013 mbar and 0 °C. Tolerance +/-3%. See notes on page 6.




### TEMPERATURE RISE

Temperature rise  $\Delta T$  measured directly at in- and outlet. Ambient condition of 1013 mbar and 20 °C. All duty points on characteristics curves are in thermal equilibrium<sup>®</sup>. Tolerance +/-5 °C.





### POWER

Motor power  $P$  delivered at impeller shaft. Ambient condition of 1013 mbar and 20 °C. All duty points on characteristics curves are in thermal equilibrium<sup>®</sup>. Tolerance +/-5%. Accurate data on current consumption for specific duty points available on request.





# DB307/311/300 1-phase



## SOUND LEVEL PRESSURE DB307 1-phase





## SOUND LEVEL VACUUM DB307 1-phase



## SOUND LEVEL PRESSURE DB311 1-phase




## SOUND LEVEL VACUUM DB311 1-phase




## DB307/311/300 1-phase

### DIMENSIONS DB307 & DB311



### DIMENSIONS DB300



- all dimensions in mm except in- and outlet connection
- CAD models available in STEP format
- tolerance  $\pm 2$  mm
- in case of discrepancy between dimensional drawing and CAD model, dimensions in dimensional drawing take precedence

## DB307/311/300 1-phase

### ORDERING INFORMATION

<b>53</b>	<b>DB</b>	<b>S</b>	<b>5</b>	<b>75</b>	<b>U...-..</b>	<b>ss</b>	<b>HT</b>	<b>RS</b>	<b>FE</b>	<b>IP56</b>	<b>Q</b>	<b>G</b>	<b>Ex</b>	<b>C...</b>
51: single phase / 53: three phase	Dutair Blower	S: Double stage serial blower P: Double stage parallel blower	Blower size	Motor size	Optional special motor voltage e.g. U500-50: 500 V at 50 Hz version	Optional bearing material ss: stainless steel	Optional bearing lubrication <sup>⑧</sup> HT: high temp. / LT: low temp.	Optional bearing material RS: Improved resistance against moisture	Optional seal on motor shaft FE: PTFE seal / Vit: Viton seal	Optional motor protection: IP56 / IP65, for IP56 specific mounting position	Optional Q: anti condensation heating 230 V	Optional G: blower in gas-tight version available for single stage blowers	Optional ATEX non-sparking version ATEX Ex II Cat 3G/3D Ex-na	Optional painting: standard RAL7023 e.g. C7035: RAL7035

### COMMENTS

**WARNING:** Comparing performance data can be misleading. Dutair specifications are based on a thermal equilibrium<sup>®</sup> for all duty points along the characteristics curves in this document. Many commercial based flow characteristics curves defined as m<sup>3</sup>/h air at 20 °C, 1013 mbar(a) and +/-10 % tolerance but can be up to 40 % higher than accurate characteristics curves defined as Nm<sup>3</sup>/h air at 0 °C, 1013 mbar(a), thermal equilibrium<sup>®</sup> duty points and +/-3 % tolerance as specified in this Dutair document.

The performance measurements are executed with instruments calibrated by DNV KEMA and are traceable to primary and/or internationally accepted measurement standards.

- ① Maximum shaft power allowed at continuous operation.  
Rated output electric motor in accordance with NEN-EN-IEC 60034-1.
- ② Allowed supply voltage tolerance 5 %. Consult your Dutair dealer for different supply voltages.
- ③ Protection class in accordance with NEN-EN-IEC 60034-5.
- ④ PTC thermistors connected in series fitted in main windings and auxiliary windings.
- ⑤ N/a.
- ⑥ N/a.
- ⑦ Free field equivalent continuous sound pressure level A-weighted L<sub>eq</sub>[dB(A)].  
Unless specified L<sub>eq</sub>[dB(A)] rated at 50 % of maximum pressure at 50 Hz. Tolerance +/- 2 dB(A).  
Conditions as note ⑬.
- ⑧ Thermal equilibrium is the state reached when the temperature rises of several parts of the machine as well as the temperature rise between in- and outlet do not vary by more than a gradient of 2°C per hour.
- ⑨ Operation at 230 V within range of 50 to 60 Hz.
- ⑩ N/a.
- ⑪ N/a.
- ⑫ Free field class 1 octave band measurements in accordance with IEC 61260 unweighted L<sub>p</sub>[dB(Z)].  
Tolerance +/- 5 dB(Z). Conditions as note ⑬.
- ⑬ Measurements at 1 m distance with in- and outlet duct connected to the blower on a reflective surface.  
Class 1 sound level meter Delta Ohm HD2010UC/A according to IEC 61672-1.  
Acoustic calibration prior to measurements with class 1 calibrator HD2020ACC according to IEC 60942.
- ⑭ Standard ambient temperature range -20...+40°C.